

17/25 Versa-Lift with 3 Counterweight Slabs

Slab Weight (lbs)

1500

Number of Slabs

3

Standard Wheel Base (in)

72

Lift Capacities w/Forks Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Fork Face (in)	24	18700	20800	22900	25000
	36	15100	16800	18500	20200
	48	12600	14100	15500	16900
	60	10900	12100	13300	14600
	72	9500	10600	11700	12800
	84	8500	9500	10400	11400

Lift Capacities w/Forks & Boom (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	18400	20600	22800	25000
	24	14600	16400	18100	19900
	36	12100	13600	15000	16500
	48	10300	11500	12800	14100
	60	8900	10000	11100	12200
	72	7800	8900	9900	10800
	84	7000	8000	8900	9700
	96	6400	7200	8000	8800

Lift Capacities w/Boom Only (lbs)					
		Counterweight Extension (in)			
		0	12	24	36
Load Center From Boom Face (in)	12	19100	21300	23500	25800
	24	15200	17000	18700	20500
	36	12600	14000	15500	17000
	48	10700	11900	13200	14500
	60	9300	10400	11500	12600
	72	8200	9200	10200	11200
	84	7300	8300	9100	10000
	96	6600	7500	8300	9100

****All Load Capacities are rated with the mast vertical.*