

60/80 Versa-Lift with 6 Counterweight Slabs

Slab Weight (lbs)
5000

Number of Slabs
6

Standard Wheel Base
120

		Lift Capacities w/Forks Only (lbs)				
		Counter Weight Extension (in)				
		0	12	24	36	48
Load Center From Fork Face (in)	22	69400	76900	84300	91800	99300
	36	55100	61000	67000	72900	78800
	48	46900	51900	56900	62000	67000
	60	40700	45100	49500	53900	58300
	72	36000	39900	43800	47700	51500
	84	32300	35800	39300	42700	46200

		Lift Capacities w/Boom Only (lbs)				
		Counter Weight Extension (in)				
		0	12	24	36	48
Load Center From Boom Face (in)	6	64900	72300	79600	86900	94300
	24	48900	54400	60000	65500	71000
	36	42000	46800	51500	56200	61000
	48	36800	41000	45100	49300	53400
	60	32800	36500	40200	43900	47600
	72	29500	32800	36200	39500	42800
	84	26900	29900	32900	35900	39000
	96	24600	27400	30200	33000	35800
	108	22700	25300	27900	30500	33000
	120	21100	23500	25900	28300	30700

		Lift Capacities w/Forks & Boom (lbs)				
		Counter Weight Extension (in)				
		0	12	24	36	48
Load Center From Boom Face (in)	24	46900	52400	58000	63500	69000
	36	40300	45000	49800	54500	59300
	48	35300	39500	43600	47800	51900
	60	31400	35100	38800	42500	46200
	72	28300	31600	35000	38300	41600
	84	25800	28800	31800	34900	37900

****All Load Capacities are Rated with the Mast Vertical*